

FEATURES / SPECIFICATIONS

- Floor standing back-to-wall close-coupled toilet
- Vitreous china vortex wash-down bowl
- Dual-flush
- Dual trap outlet: 180 mm, Ø102 mm
- 400 mm bowl height (w/out seat)
- Installed dimensions: 630 x 355 x 785 mm
- 32 kg ceramic bowl weight
- 11 kg ceramic cistern weight
- Double chrome button activation
- Roca inlet and flush valve
- Cistern set to 4.5/3L flush, can operate at 4/2L flush
- Dynamic water pressure: 0,1 - 10 bar
- See Roca catalogue or web for available colours



MODELS / REFERENCES

Reference		Description	Comments
A342V15...	Bowl	WC FS CC 630 BTW DUAL VORTEX GR	Includes all fittings
A341V10...	Cistern	Cistern lateral inlet G3/8 (Ø19 mm)	4,5/3 L Includes valve kit
A341V11...		Cistern bottom inlet G3/8 (Ø19 mm)	4,5/3 L Includes valve kit
A341V1C...		Cistern bottom inlet G1/2 (Ø23 mm)	4,5/3 L Includes valve kit
A801F70..1	Seat & cover	Urea, metal hinges, standard close	-
A801F72..1		Urea, metal hinges, soft close	-
A801F72..2		Urea, metal hinges, soft close, slim	-

COMPATIBLE / RECOMMENDED ACCESSORIES

Reference		Description	Comments
A525164400	Angle valve	Ceramic angle valve G1/2-G3/8	-
A525164500		Ceramic angle valve G1/2-G1/2 (UK-AU)	-
AV0007900R	Outlet	S-Trap outlet pipe, rough-in 150 mm	-
-		S-Trap outlet pipe (Market), rough-in 120 mm	-
-		Straight outlet pipe (Market)	-

STANDARDS

Meets the following standards

EU	EN 33 EN 997 according to DoP EN 14124
----	--

INSTALLATION NOTES

- Install this product according to installations instructions provided.
- Floor mounted bowl, lateral fixing kit with corrosion resistant screws and chrome caps.
- Cistern is fixed directly to the close-coupled toilet with two stainless steel screws, without the need for wall fixing installation.
- Cistern, seat & cover and recommended accessories are not included. They must be ordered separately.

PRODUCT DIAGRAM

