Classica Slabs

SCAN HERE

Simple & stylish.

Classica Slabs have a stylish, simple look. A variety of shades and size options, Classica Slabs have the flexibility to blend with contemporary and traditional developments.

- Superb hard-wearing surface
- Vibrant long-lasting colours
- Cost-effective alternative

PrimeTop®

Finish

S
Smooth

Also available as

Permeable

Refer to relevant guidance in BS 7533

Pedestrian Use | Light Traffic | Commercial Traffic | BIM Level 2





600 x 600mm



450 x 450mm



400 x 400mm

Sizes



50mm
40mm
35mm

Depths

Classica Slabs



Specification

PrimeTop®

Product type	Concrete Paving Slab
Manufactured to	BS EN 1339:2003
Surface Layer	Hard-wearing surface layer with a minimum of 4mm and >390kgs/m^3 cement
Chamfer	Chamfered
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
Bending Strength	**Less than 50mm deep** Characteristic tensile splitting strength not less than 3.6 MPa **50mm or greater** Characteristic tensile splitting strength of >5MPa (Class 3)
Slip/Skid Resistance	Mean polished skid resistance value (PSRV) >45 Mean unpolished skid resistance value (USRV) >45
Installed to	BS 7533-102:2025
NSS	**Plus** Q25 315 **Create** 45-20-64/395
Tolerances on Dimensions (mm)	Length ±2mm, width ±2mm, thickness ±3mm
Abrasion Resistance (mm)	≤ 23mm (Wide Wheel Abrasion Test) Class 3
Durability (Freeze-thaw)	≤ 1.0 kg/m^2 as a mean with no individual value > 1.5 kg/m^2 Class 3
External Fire Performance	Deemed to satisfy when used for roofing
Reaction to fire	Class A1
Applications	Refer to the relevant part of BS 7533 for the correct sub-base design and the most suitable product size for your application. Available from www.bsigroup.com
Energy used	100% renewable energy
Water used	100% from our rainwater harvesting system and groundwater bore hole
Recycled content	Not less than 5%
Carbon Footprint	**EPD Verified** *(2020)* **400x400x40mm** 9.63kgCo^2e/m^2 **450x450x35mm** 8.76kgCo^2e/m^2 **450x450x50mm** 11.87kgCo^2e/m^2 **600x600x50mm** 12.46kgCo^2e/m^2
Recyclable	100% of this product can be recycled
Manufacturing & Delivery	From one location within the UK
breeam rating www.**bre**.co.uk	**A**, according to the Green Guide to Specification, 4th Edition 2009. **A+**, can be achieved by using a recycled sub-base.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 Quality Management. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BES 6001.

Classica Slabs



Natural



Charcoal



Buff



Golden



Stock

product	size (mm)	edge	colours available	in stock	no. per m²	no. per pack	no. per pallet	weight kg per pack GB	weight kg per pack NI/ROI
Classica Slabs **BIM**	600 x 600 x 50	Chamfered	Natural	YES	2.78	20	20	852	842
	600 x 600 x 40	Chamfered	Buff, Charcoal, Natural	YES	2.78	30	30	1051	1051
	450 x 450 x 50	Chamfered	Buff, Charcoal, Natural	YES	4.94	20	80	478	468
	450 x 450 x 35	Chamfered	Buff, Charcoal, Natural	YES	4.94	30	60	527	517
	400 x 400 x 40	Chamfered	Charcoal	YES	6.25	25	100	413	403
			Golden, Natural			90	90	1450	1450

BIM - This product is available to download from our website in BIM Level 2 format.

Contact Us
GB: 0844 800 5736
NI: 028 7964 2411
ROI: 048 7964 2411

Email
technical@tobermore.co.uk
sales@tobermore.co.uk