Hydropave Pedesta

SCAN HERE

Versatile permeable paving.

Hydropave Pedesta has a smooth surface and a timeless appeal. Available in four colours, this paving provides you with plenty of scope to create patterns and designs.

- Functions as a SuDS paving system
- Superb hard-wearing smooth surface
- Vibrant long-lasting colours

200 x 100mm

Sizes

60mm
80mm

Depths

PrimeTop®

S
Smooth

Finish

Pedestrian Use | Light Traffic | Commercial Traffic

BIM Level 2

Refer to relevant guidance in BS 7533



Hydropave Pedesta



Specification

PrimeTop®

Product type	Concrete Paving Block
Manufactured to	BS EN 1338:2003
Surface Layer	Hard-wearing surface layer with a minimum layer of 4mm and >350kgs/m^3 cement
Surface Finish	Smooth
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
Drainage Void Width	5.5% to accommodate correct grit grading, reduce maintenance and maximise drainage flow rate
Tensile Splitting Strength	Typical tensile splitting strength of >3.6MPa
Slip/Skid Resistance	Mean polished skid resistance value (PSRV) >45 Mean unpolished skid resistance value (USRV) >45
Installed to	BS7533-103:2026
ᑎᔑᕋ	**Plus** Q24 115 **Create** 45-20-64/400 **Plus** Q24 117 **Create** 45-20-64/400 **Plus** Q24 119 **Create** 45-20-64/400
Tolerances on Dimensions (mm)	Length ±2mm, width ±2mm, thickness ±3mm
Abrasion Resistance (mm)	≤ 23mm (Wide Wheel Abrasion Test) Class 3
Durability (Freeze-thaw)	≤ 1.0 kg/m^2 as a mean with no individual value > 1.5 kg/m^2 Class 3
External Fire Performance	Deemed to satisfy when used for roofing
Reaction to fire	Class A1
Applications	Refer to the relevant part of BS 7533 for the correct sub-base design and the most suitable product size for your application. Available from www.bsigroup.com
Energy used	100% renewable energy
Water used	100% from our rainwater harvesting system and groundwater bore hole
Recycled content	Not less than 12%
Carbon Footprint	**EPD Verified** *(2020)* **60mm** 14.17kgCo^2e/m^2 **80mm** 20.98kgCo^2e/m^2
Recyclable	100% of this product can be recycled
Manufacturing & Delivery	From one location within the UK
breeam rating www.**bre**.co.uk	**60mm:A**, according to the Green Guide to Specification, 4th Edition 2009. **A+**, can be achieved by using a recycled sub-base. **80mm:B**, according to the Green Guide to Specification, 4th Edition 2009. **A**, can be achieved by using a recycled sub-base.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 Quality Management. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BES 6001.

Hydropave Pedesta



Stock

product	size (mm)	colours available	edge	in stock	m² per pack	m² per slice	no. per m²	no. per pack	weight kg per pack GB	weight kg per pack NI/ROI
Hydropave Pedesta BIM	200 x 100 x 60	Bracken, Brindle, Charcoal, Natural	Chamfer	YES	13.44	2.24	50	672	1808	1798
	200 x 100 x 80	Bracken, Brindle,Charcoal, Natural	Pencil chamfer	YES	9.6	1.6	50	480	1732	1722

BIM - This product is available to download from our website in BIM Level 2 format.

Bracken



Brindle



Charcoal



Natural



Contact Us
GB: 0844 800 5736
NI: 028 7964 2411
ROI: 048 7964 2411

Email
technical@tobermore.co.uk
sales@tobermore.co.uk