SCAN HERE

Textured Kerb

Cost effective decorative kerb with a shot blasted finish.

Textured Kerb offers a rustic and understated aesthetic which complements a wide variety of paving and other hard surfaces.

- Features an exposed granular surface
- Shot blasted textured finish
- A step up from standard precast concrete kerbs
- Budget friendly decorative kerb

T
Textured

Finish

Pedestrian Use

Light Traffic

Commercial Traffic

BIM Level 2



Size



Textured Kerb



Specification

Product type	Concrete Kerb
Manufactured to	BS EN 1340: 2003
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
Breaking / Bending Strength: Transverse Test	Characteristic bending strength of 3.5 MPa with no individual result less than 2.8 MPa
Durability (Freeze-thaw)	≤ 1.0 kg/m² as a mean with no individual value > 1.5 kg/m² Class 3
Abrasion Resistance (mm)	≤ 23mm (Wide Wheel Abrasion Test)
Slip/Skid resistance	Mean polished skid resistance value (PSRV) >45, Mean unpolished skid resistance value (USRV) >45
Installed to	BS 7533-102:2025
ᑎᔭᕋ	**Plus** Q10 110 **Create** 45-20-64/370 **Plus** Q10 110 **Create** 45-20-64/365
Applications	Residential and Commercial when designed in accordance with the latest British Standard. Available from **www.bsigroup.com**
Energy used	100% renewable energy
Water used	100% from our rainwater harvesting system and groundwater bore hole
Recycled content	Not less than 5%
Carbon footprint	8.82kgCo2e /LM
Recyclable	100% of this product can be recycled
Manufacturing & Delivery	From one location within the UK
breeam rating www.**bre**.co.uk	Refer to the Green Guide to Specification, 4th Edition 2009.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 quality. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BES 6001.

Textured Kerb



Stock

product	size (mm)	colours available	in stock	no. per pack	weight kg per pack GB	weight kg per pack NI/ROI
Textured Kerb BIM	125 x 255 x 915	Natural	YES	16	1112	1102
Textured Kerb Dropper (specify left or right hand dropper)	125 x 255/150 x 915	Natural	YES	16	842	832
Textured Dropper Kerb	125 x 150 x 915	Natural	YES	32	1354	1344
Textured Kerb Corner External or Internal Corner	125 x 255 x 915/790	Natural	YES	12	834	834
Textured Kerb End Unit	125 x 255 x 455	Natural	YES	32	1102	1102

BIM - This product is available to download from our website in BIM Level 2 format.

Natural



Contact Us
GB: 0844 800 5736
NI: 028 7964 2411
ROI: 048 7964 2411

Email
technical@tobermore.co.uk
sales@tobermore.co.uk