Textured Slabs

SCAN HERE

Stylish granular surface.

Textured Slabs have a modern and natural look that blends beautifully with a variety of other products. Manufactured with a hard-wearing granular surface, these slabs are both stylish and hard-wearing.

- Superb hard-wearing textured surface
- Vibrant long-lasting colours
- Natural appearance

PrimeTop®

T
Textured

Finish

Pedestrian Use | Light Traffic | Commercial Traffic | BIM Level 2

Refer to relevant guidance in BS 7533





600 x 400mm



450 x 450mm



400 x 400mm

Sizes



35mm
40mm
50mm

Depths

Textured Slabs





Specification

PrimeTop

Product type	Concrete Paving Slab
Manufactured to	BS EN 1339:2003
Surface Layer	Hard-wearing surface layer with a minimum of 4mm and >390kgs/m^3 cement
Chamfer	Chamfered
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
Bending Strength	**Less than 50mm deep** Characteristic tensile splitting strength not less than 3.6 MPa **50mm or greater** Characteristic tensile splitting strength of >5MPa (Class 3)
Slip/Skid Resistance	Mean polished skid resistance value (PSRV) >45 Mean unpolished skid resistance value (USRV) >45
Installed to	BS 7533-102:2025
NBS	**Plus** Q25 315 **Create** 45-20-64/395
Tolerances on Dimensions (mm)	Length ±2mm, width ±2mm, thickness ±3mm
Abrasion Resistance (mm)	≤ 23mm (Wide Wheel Abrasion Test) Class 3
Durability (Freeze-thaw)	≤ 1.0 kg/m² as a mean with no individual value > 1.5 kg/m² Class 3
External Fire Performance	Deemed to satisfy when used for roofing
Reaction to fire	Class A1
Applications	Refer to the relevant part of BS 7533 for the correct sub-base design and the most suitable product size for your application. Available from www.bsigroup.com
Energy used	100% renewable energy
Water used	100% from our rainwater harvesting system and groundwater bore hole
Recycled content	Not less than 5%
Carbon Footprint	**EPD Verified** *(2020)* **400x400x40mm** 9.06kgCo²e/m² **450x450x35mm** 8.72kgCo²e/m² **450x450x50mm** 12.08kgCo²e/m² **600x400x50mm** 12.67kgCo²e/m² **600x600x40mm** 9.96kgCo²e/m² **600x600x50mm** 12.09kgCo²e/m²
Recyclable	100% of this product can be recycled
Manufacturing & Delivery	From one location within the UK
breeam rating www.**bre**.co.uk	**A**, according to the Green Guide to Specification, 4th Edition 2009. **A+**, can be achieved by using a recycled sub-base.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 Quality Management. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BES 6001.

Textured Slabs



Stock

product	size (mm)	edge	colours available	in stock	no. per m²	no. per pack	no. per pallet	weight kg per pack GB	weight kg per pack NI/ROI
Textured Slabs BIM	600 x 600 x 50	Chamfered	Buff, Natural	YES	2.78	20	20	843	833
	600 x 600 x 40	Chamfered	Buff, Charcoal, Natural	YES	2.78	30	30	1051	1051
	600 x 400 x 50	Chamfered	Charcoal, Natural	YES	2.78	24	24	590	580
	450 x 450 x 50	Chamfered	Buff, Charcoal, Natural	YES	4.94	20	80	468	468
	450 x 450 x 35	Chamfered	Buff, Charcoal, Natural	YES	4.94	30	60	527	517
	400 x 400 x 40	Chamfered	Charcoal, Natural	YES	6.25	25	100	410	400
			Golden			90	90	1450	1450

BIM - This product is available to download from our website in BIM Level 2 format.

Natural



Charcoal



Buff



Golden



Contact Us
GB: 0844 800 5736
NI: 028 7964 2411
ROI: 048 7964 2411

Email
technical@tobermore.co.uk
sales@tobermore.co.uk