



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK ARDATEC 2K FLEX A
Supersedes date 11-Jun-2025

Revision date 24-Oct-2025
Revision Number 1.05

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK ARDATEC 2K FLEX A
Form This substance/ mixture contains nanoforms

Other means of identification

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Building and construction work: Fillers, putties, plasters, modelling clay
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik GmbH
Industriestrasse 3 – 11
33829 Borgholzhausen, Germany
Tel: +49 (0) 5425 / 801 0
Fax: +49 (0) 5425 / 801 140

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Ireland **NPIC - National Poison Information Centre**
Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)
Healthcare Professionals: +353 (01) 8092566 (24 hour service)
United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)
Europe 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin irritation	Category 2 - (H315)
Serious eye damage	Category 1 - (H318)
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Category 3 Target organ effects: Respiratory irritation.	

2.2. Label elements

Contains Portland Cement; Flue dust, Cement Portland

SAFETY DATA SHEET

BOSTIK ARDATEC 2K FLEX A
Supersedes date 11-Jun-2025

Revision date 24-Oct-2025
Revision Number 1.05



Signal word
Danger

Hazard statements

H315 - Causes skin irritation.
H318 - Causes serious eye damage.
H335 - May cause respiratory irritation.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P261 - Avoid breathing dust
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves, eye protection and face protection
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap
P332 + P313 - If skin irritation occurs: Get medical advice/attention
P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

Cement product for which the amount of chromium VI was decreased to < 0,0002 % by a reduction agent (related to the total dry weight). If the storage conditions are not appropriate (exposure to humidity) or the storage period is exceeded, the effectiveness of the present reducing agent can diminish prematurely, and the cement/binder can become skin sensitizing (H317 or EUH203, respectively). This product is part of a kit. Please also refer to the SDS for the other component(s) of the kit.

2.3. Other hazards

When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. Product dust may be irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness or cracking.

PBT & vPvB

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No. (Index No.)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
---------------	----------	---------------------------	--------------------	---	------------------------------------	----------	----------------------	-------

SAFETY DATA SHEET

BOSTIK ARDATEC 2K FLEX A
Supersedes date 11-Jun-2025

Revision date 24-Oct-2025
Revision Number 1.05

Quartz 14808-60-7	40 - <80	[5]	238-878-4	[B]	-	-	-	-
Portland Cement 65997-15-1	20 - <25	[5]	266-043-4	Skin Irrit. 2 (H315) Eye Dam. 1 (H318) STOT SE 3 (H335)	-	-	-	-
Flue dust, Cement Portland 68475-76-3	1 - <2.5	01-2119486767 -17-XXXX	270-659-9	Skin Irrit. 2 (H315) Eye Dam. 1 (H318) STOT SE 3 (H335)	-	-	-	-
Quartz (fine fraction) 14808-60-7	0.1 - <0.3	[5]	238-878-4	STOT RE 1 (H372)	-	-	-	-

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(b) and Annex V of REACH Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes
[B] - Substance with a Community workplace exposure limit

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Quartz	238-878-4	14808-60-7	-	-	-	-	-
Portland Cement	266-043-4	65997-15-1	-	-	-	-	-
Flue dust, Cement Portland	270-659-9	68475-76-3	-	-	-	-	-
Quartz (fine fraction)	238-878-4	14808-60-7	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand. Take a copy of the Safety Data Sheet when going for medical treatment.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
Skin contact	Brush off loose particles from skin. Remove material from skin immediately. Take off contaminated clothing and wash it before reuse.
Ingestion	If swallowed, rinse mouth with water (only if the person is conscious). Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.

SAFETY DATA SHEET

BOSTIK ARDATEC 2K FLEX A
Supersedes date 11-Jun-2025

Revision date 24-Oct-2025
Revision Number 1.05

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Dust irritates eyes and air passages. Causes serious eye damage. Irritating to skin. Inhalation of dust in high concentration may cause irritation of respiratory system. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.

Effects of Exposure No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Product itself does not burn.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO₂).

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Methods for containment Cover powder spill with plastic sheet or tarp to minimise spreading and keep powder dry. Prevent dust cloud.

Methods for cleaning up Use appropriate personal protective equipment (PPE). Carefully shovel or sweep up

SAFETY DATA SHEET

BOSTIK ARDATEC 2K FLEX A
Supersedes date 11-Jun-2025

Revision date 24-Oct-2025
Revision Number 1.05

spilled material and place in suitable container. Avoid generating dust.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling This product is part of a kit. Please also refer to the SDS for the other component(s) of the kit. Ensure adequate ventilation. Avoid generation of dust. Use personal protection equipment. Take off contaminated clothing and wash it before reuse.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep the packing dry and well sealed to prevent contamination and absorption of humidity. For cements treated with a Cr (VI) reducing agent the effectiveness of the reducing agent diminishes with time and if not stored in an appropriate manner. Keep away from food, drink and animal feedingstuffs.

7.3. Specific end use(s)

Specific use(s)
 Building and construction work. Fillers, putties, plasters, modelling clay.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Quartz 14808-60-7	TWA: 0.1 mg/m ³ ;	TWA: 0.1 mg/m ³ ; respirable dust STEL: 0.3 mg/m ³ ;	TWA: 0.1 mg/m ³ ; respirable fraction STEL: 0.3 mg/m ³ ; respirable
Portland Cement 65997-15-1	-	TWA: 1 mg/m ³ ; respirable fraction STEL: 3 mg/m ³ (calculated); respirable fraction	TWA: 10 mg/m ³ ; inhalable dust TWA: 4 mg/m ³ ; respirable dust STEL: 30 mg/m ³ ; inhalable dust STEL: 12 mg/m ³ ; respirable dust
Dust RR-12364-8	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³	TWA: 10 mg/m ³ ; inhalable dust TWA: 4 mg/m ³ ; respirable dust STEL: 30 mg/m ³ ; inhalable dust STEL: 12 mg/m ³ ; respirable dust
Quartz (fine fraction) 14808-60-7	TWA: 0.1 mg/m ³ ;	TWA: 0.1 mg/m ³ ; respirable dust STEL: 0.3 mg/m ³ ;	TWA: 0.1 mg/m ³ ; respirable fraction STEL: 0.3 mg/m ³ ; respirable

SAFETY DATA SHEET

BOSTIK ARDATEC 2K FLEX A
Supersedes date 11-Jun-2025

Revision date 24-Oct-2025
Revision Number 1.05

Distillates, petroleum, hydrotreated heavy naphthenic , <3% DMSO 64742-52-5	-	TWA: 5 ppm; inhalable STEL: 15 ppm (calculated;pure;highly and severely refined); air
---	---	--

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

- Eye/face protection** Goggles Face protection shield. Tight sealing safety goggles. Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166
- Hand protection** Wear suitable gloves. Recommended Use: Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time for the mentioned glove material is in general greater than 480 min. Unsuitable gloves materials: Leather. Gloves must conform to standard EN 374
- Skin and body protection** Suitable protective clothing.
- Respiratory protection** Avoid generation of dust. In case of inadequate ventilation wear respiratory protection. Particle filter device (DIN EN 143). No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
- Recommended filter type:** Wear a respirator conforming to EN 140 with Type P2/P3 filter or better. White.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Powder
Colour	Grey
Odour	Characteristic.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	Not applicable . °C	Not applicable
Initial boiling point and boiling range	No data available	Not applicable
Flammability	No data available	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	No data available	Not applicable
Autoignition temperature	No data available	
Decomposition temperature		None known
pH	No data available	Not applicable.
pH (as aqueous solution)	> 11	solution (75 %)
Kinematic viscosity	Not applicable . mm ² /s	Not applicable
Dynamic viscosity	Not applicable .	Not applicable
Water solubility	Reacts with water. Cement based products react and solidify in contact with water	
Solubility(ies)	No data available	

SAFETY DATA SHEET

BOSTIK ARDATEC 2K FLEX A
Supersedes date 11-Jun-2025

Revision date 24-Oct-2025
Revision Number 1.05

Partition coefficient	No data available
Vapour pressure	No data available
Relative density	No data available
Bulk density	ca. 1.4 - 1.5 g/cm ³
Density	No data available
Relative vapour density	No data available
Particle characteristics	
Particle Size	No information available
Particle Size Distribution	No information available

9.2. Other information

Solid content (%)	100	
Softening point	Not applicable	
VOC content		No data available

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available Not applicable .

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Keep away from Incompatible materials. Stable under recommended storage conditions.

Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Aluminium.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

SAFETY DATA SHEET

BOSTIK ARDATEC 2K FLEX A
Supercedes date 11-Jun-2025

Revision date 24-Oct-2025
Revision Number 1.05

Inhalation	Inhalation of dust in high concentration may cause irritation of respiratory system.
Eye contact	Causes serious eye damage.
Skin contact	Causes skin irritation.
Ingestion	Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. Prolonged contact may cause redness and irritation.

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	>2000 mg/kg
ATEmix (dermal)	>2000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/L
ATEmix (inhalation-vapour)	>20 mg/L

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz	>2000 mg/kg (Rattus)	-	-
Portland Cement	-	>2000 Kg/mg (Lapin)	>5 g/m ³ (Rattus)
Flue dust, Cement Portland	-	LD50 ≥ 2000 mg/kg (Rat) OECD 402	> 6.04604 mg/L (Rat) 4 h
Quartz (fine fraction)	>2000 mg/kg (Rattus)	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes serious eye damage.
Respiratory or skin sensitisation	Based on available data, the classification criteria are not met.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT - single exposure	May cause respiratory irritation.

SAFETY DATA SHEET

BOSTIK ARDATEC 2K FLEX A
Supersedes date 11-Jun-2025

Revision date 24-Oct-2025
Revision Number 1.05

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

11.2.2. Other information

Other adverse effects No information available.

Note: This product is part of a kit. Please also refer to the SDS for the other component(s) of the kit.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment Based on available data, the classification criteria are not met.

Chemical name	PBT and vPvB assessment
Flue dust, Cement Portland	PBT assessment does not apply

12.6. Endocrine disrupting properties **Endocrine disrupting properties**

Endocrine disruption for the environment Based on available data, the classification criteria are not met.

12.7. Other adverse effects **Other adverse effects**

Other adverse effects No information available.

PMT or vPvM properties Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

BOSTIK ARDATEC 2K FLEX A
Supercedes date 11-Jun-2025

Revision date 24-Oct-2025
Revision Number 1.05

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03 10 13 06 particulates and dust (except 10 13 12 and 10 13 13) Cured product can be treated as construction waste. In the management of larger quantities consult with local authorities and local waste disposal company 10 13 14 waste concrete and concrete sludge
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

IMDG

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	None
14.7 Maritime transport in bulk according to IMO instruments	
Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

SAFETY DATA SHEET

BOSTIK ARDATEC 2K FLEX A
Supersedes date 11-Jun-2025

Revision date 24-Oct-2025
Revision Number 1.05

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Portland Cement	65997-15-1	47

47 where product supplied with reducing agent the packaging must be marked with the storage conditions and storage period appropriate to maintaining the activity of the reducing agent to keep the content of soluble chromium VI below 2mg/Kg.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Ozone-depleting substances (ODS) regulation (EC) 2024/590

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

Regulations on drug precursors (EC) No 111/2005 (export) and 273/2004 (internal trade)

This product does not contain any substance(s) on the Drug Precursors list.

National regulations

15.2. Chemical safety assessment

Not applicable

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

SAFETY DATA SHEET

BOSTIK ARDATEC 2K FLEX A
Supersedes date 11-Jun-2025

Revision date 24-Oct-2025
Revision Number 1.05

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H315 - Causes skin irritation
H318 - Causes serious eye damage
H335 - May cause respiratory irritation
H372 - Causes damage to organs through prolonged or repeated exposure

SVHC: Substances of Very High Concern for Authorisation:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances
STOT RE: Specific target organ toxicity - Repeated exposure
STOT SE: Specific target organ toxicity - Single exposure
EWC: European Waste Catalogue
LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
IATA: International Air Transport Association
ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG: International Maritime Dangerous Goods
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	SK*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Chronic aquatic toxicity	Calculation method
Acute aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
European Chemicals Agency (ECHA) (ECHA_API)
U.S. Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGL(s))
International Uniform Chemical Information Database (IUCLID)
Japan National Institute of Technology and Evaluation (NITE)
NIOSH (National Institute for Occupational Safety and Health)
International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications
International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program
International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

SAFETY DATA SHEET

BOSTIK ARDATEC 2K FLEX A
Supersedes date 11-Jun-2025

Revision date 24-Oct-2025
Revision Number 1.05

Revision date 24-Oct-2025

Revision Note SDS sections updated: 4 5 7 15 16

Training Advice When working with hazardous materials, regular training of operators is required by law

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878, and Regulation (EC) No. 1272/2008

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet