



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**CEMENTONE WATERSEAL**  
Supersedes date 16-May-2023

Revision date 08-Jan-2025  
Revision Number 2

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product Name CEMENTONE WATERSEAL

### Other means of identification

Pure substance/mixture Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Primers, Sealers, and Undercoaters

Uses advised against None known

### 1.3. Details of the supplier of the safety data sheet

Company Name	Supplier
Bostik SA	Bostik Industries Limited
420 rue d'Estienne d'Orves	Newtown, Swords
92700 Colombes	Co. Dublin Ireland
FRANCE	Tel: +353 (1) 8624900
Tel: +33 (0)1 49 00 90 00	Fax: +353 (1) 8402186

E-mail address SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

Ireland	NPIC - National Poison Information Centre
	Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)
	Healthcare Professionals: +353 (01) 8092566 (24 hour service)
United Kingdom	Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)
Europe	112

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids	Category 3 - (H226)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Category 3 Target organ effects: Narcotic effects.	
Specific target organ toxicity (repeated exposure)	Category 1 - (H372)
Aspiration hazard	Category 1 - (H304)
Hazardous to the aquatic environment - chronic	Category 2 - (H411)

### 2.2. Label elements

Contains Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%); Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics ; Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics; 1,2,4-trimethylbenzene

# SAFETY DATA SHEET

**CEMENTONE WATERSEAL**  
Supersedes date 16-May-2023

Revision date 08-Jan-2025  
Revision Number 2



**Signal word**  
Danger

## Hazard statements

H226 - Flammable liquid and vapour.  
H304 - May be fatal if swallowed and enters airways.  
H336 - May cause drowsiness or dizziness.  
H372 - Causes damage to organs through prolonged or repeated exposure.  
H411 - Toxic to aquatic life with long lasting effects.

## EU Specific Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking

## Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand  
P102 - Keep out of reach of children  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P260 - Do not breathe mist/vapours/spray  
P271 - Use only outdoors or in a well-ventilated area  
P273 - Avoid release to the environment  
P280 - Wear protective gloves and eye/face protection  
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor  
P331 - Do NOT induce vomiting  
P391 - Collect spillage  
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed  
P501 - Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable

## Additional information

This product requires child resistant fastenings if supplied to the general public. This product requires tactile warnings if supplied to the general public.

## 2.3. Other hazards

Causes mild skin irritation.

## PBT & vPvB

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No (EU Index No)	Classification according to Regulation (EC) No.	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
---------------	----------	---------------------------	---------------------	---	------------------------------------	----------	----------------------	-------

# SAFETY DATA SHEET

**CEMENTONE WATERSEAL**  
**Supersedes date** 16-May-2023

**Revision date** 08-Jan-2025  
**Revision Number** 2

				1272/2008 [CLP]				
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) RR-91855-8	40 - <80	01-2119458049 -33-XXXX	919-446-0	STOT SE 3 (H336) STOT RE 1 (H372) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 3 (H226) (EUH066)	-	-	-	-
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics RR-100224-0	>25 - <40	01-2119463258 -33-XXXX	919-857-5	STOT SE 3 (H336) Asp. Tox. 1 (H304) (EUH066) Flam. Liq. 3 (H226)	-	-	-	-
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics RR-108541-2	1 - <5	01-2119456620 -43-XXXX	926-141-6	Asp. Tox. 1 (H304) (EUH066)	-	-	-	-
1,2,4-trimethylbenzene 95-63-6	1 - <3	01-2119472135 -42-XXXX	202-436-9 (601-043-00-3)	Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 3 (H226)	-	-	-	-
Xylenes (o-, m-, p-isomers) 1330-20-7	1 - <2.5	01-2119488216 -32-XXXX	215-535-7 (601-022-00-9)	Acute Tox. 4 (H312) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335) STOT RE 2 (H373) Asp. Tox. 1 (H304) Aquatic Chronic 3 (H412) Flam. Liq. 3 (H226)	-	-	-	C
Octane and isomers UNKNOWN	0.1 - <0.3	No data available	-	Skin Irrit. 2 (H315) STOT SE 3 (H336) Asp. Tox. 1 (H304) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) Flam. Liq. 2 (H225)	-	1	1	-

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

Note C - Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

**Full text of H- and EUH-phrases: see section 16**

## Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

# SAFETY DATA SHEET

**CEMENTONE WATERSEAL**  
**Supersedes date** 16-May-2023

**Revision date** 08-Jan-2025  
**Revision Number** 2

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0	RR-91855-8	-	3400	-	-	-
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	919-857-5	RR-100224-0	6000	5001	-	-	-
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	RR-108541-2	-	-	-	-	-
1,2,4-trimethylbenzene	202-436-9 (601-043-00-3)	95-63-6	-	3163.16	-	-	-
Xylenes (o-, m-, p-isomers)	215-535-7 (601-022-00-9)	1330-20-7	2500	1990	4.8	-	-

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
<b>Inhalation</b>	Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
<b>Ingestion</b>	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical attention.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and irritation.
<b>Effects of Exposure</b>	Causes damage to organs through prolonged or repeated exposure.

# SAFETY DATA SHEET

CEMENTONE WATERSEAL  
Supersedes date 16-May-2023

Revision date 08-Jan-2025  
Revision Number 2

## 4.3. Indication of any immediate medical attention and special treatment needed

**Note to doctors** Because of the danger of aspiration, emesis or gastric lavage should not be used unless the risk is justified by the presence of additional toxic substances.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

**Suitable Extinguishing Media** Dry chemical. Carbon dioxide (CO<sub>2</sub>). Water spray. Alcohol resistant foam.

**Unsuitable extinguishing media** Do not scatter spilled material with high pressure water streams.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the chemical** Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

**Hazardous combustion products** Carbon oxides. Hydrocarbons. Aldehydes.

### 5.3. Advice for firefighters

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

**Other information** Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

### 6.3. Methods and material for containment and cleaning up

**Methods for containment** Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

**Methods for cleaning up** Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

# SAFETY DATA SHEET

CEMENTONE WATERSEAL  
Supersedes date 16-May-2023

Revision date 08-Jan-2025  
Revision Number 2

## 6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Advice on safe handling** Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. In case of insufficient ventilation, wear suitable respiratory equipment.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

### 7.3. Specific end use(s)

**Specific use(s)**  
Primers, Sealers, and Undercoaters.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) RR-91855-8	-	-	TWA: 350 mg/m <sup>3</sup>
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics RR-108541-2	TWA:1200 mg/m <sup>3</sup>	-	
1,2,4-trimethylbenzene 95-63-6	TWA: 20 ppm TWA: 100 mg/m <sup>3</sup>	TWA: 20 ppm TWA: 100 mg/m <sup>3</sup> STEL: 60 ppm STEL: 300 mg/m <sup>3</sup>	
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 50 ppm TWA: 221 mg/m <sup>3</sup> STEL: 100 ppm STEL: 442 mg/m <sup>3</sup> *	TWA: 50 ppm TWA: 221 mg/m <sup>3</sup> STEL: 100 ppm STEL: 442 mg/m <sup>3</sup> Sk*	TWA: 50 ppm TWA: 220 mg/m <sup>3</sup> STEL: 100 ppm STEL: 441 mg/m <sup>3</sup> Sk*
1,3,5-Trimethylbenzene	TWA: 20 ppm	TWA: 20 ppm	

# SAFETY DATA SHEET

**CEMENTONE WATERSEAL**  
**Supersedes date** 16-May-2023

**Revision date** 08-Jan-2025  
**Revision Number** 2

108-67-8	TWA: 100 mg/m <sup>3</sup>	TWA: 100 mg/m <sup>3</sup> STEL: 60 ppm STEL: 300 mg/m <sup>3</sup>	
----------	----------------------------	---	--

**Derived No Effect Level (DNEL)** No information available

<b>Derived No Effect Level (DNEL)</b>			
<b>Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	330 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	44 mg/kg bw/d	

<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	180 mg/kg bw/d	
Long term Systemic health effects worker	Inhalation	77 mg/m <sup>3</sup>	
Short term Local health effects Systemic health effects worker	Inhalation	289 mg/m <sup>3</sup>	

<b>Derived No Effect Level (DNEL)</b>			
<b>Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	71 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	26 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	26 mg/kg bw/d	

**Predicted No Effect Concentration (PNEC)** No information available.

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

## Personal protective equipment

**Eye/face protection**  
**Hand protection**

Tight sealing safety goggles. Eye protection must conform to standard EN 166  
Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves should be

# SAFETY DATA SHEET

CEMENTONE WATERSEAL  
Supersedes date 16-May-2023

Revision date 08-Jan-2025  
Revision Number 2

## Skin and body protection

replaced regularly and if there is any sign of damage to the glove material.  
Wear suitable protective clothing.

## Environmental exposure controls

Local authorities should be advised if significant spillages cannot be contained. Do not allow into any sewer, on the ground or into any body of water. Prevent product from entering drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid	
Appearance	Liquid	
Colour	Clear, colourless	
Odour	Characteristic.	
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	151 °C	
Flammability	No data available	Flammable liquid
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	38 °C	
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	Not applicable.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	20 mPa s	
Water solubility	Immiscible in water.	None known
Solubility(ies)	White spirit	None known
Partition coefficient	No data available	None known
Vapour pressure	<110 kPa	None known
Relative density	No data available	None known
Bulk density	No data available	
Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

### 9.2. Other information

Solid content (%)	7	
VOC content		737 g/L

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity No information available.

# SAFETY DATA SHEET

CEMENTONE WATERSEAL  
Supersedes date 16-May-2023

Revision date 08-Jan-2025  
Revision Number 2

## 10.2. Chemical stability

**Stability** Stable under normal conditions.

### **Explosion data**

**Sensitivity to mechanical impact** None.

**Sensitivity to static discharge** Yes.

## 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

## 10.4. Conditions to avoid

**Conditions to avoid** Heat, flames and sparks.

## 10.5. Incompatible materials

**Incompatible materials** None known based on information supplied.

## 10.6. Hazardous decomposition products

**Hazardous decomposition products** None under normal use conditions. Stable under recommended storage conditions.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

##### **Product Information**

**Inhalation** Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

**Eye contact** Specific test data for the substance or mixture is not available. May cause irritation.

**Skin contact** Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes mild skin irritation.

**Ingestion** Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and irritation.

#### Acute toxicity

##### **Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)** 21,942.30 mg/kg  
**ATEmix (dermal)** 170,567.40 mg/kg

# SAFETY DATA SHEET

CEMENTONE WATERSEAL  
Supersedes date 16-May-2023

Revision date 08-Jan-2025  
Revision Number 2

ATEmix (inhalation-gas) >20000 ppm  
ATEmix (inhalation-dust/mist) 48.40 mg/l  
ATEmix (inhalation-vapour) 942.8351 mg/l

## Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	LD50 >15000 mg/Kg (Rattus) OECD 401	LD50 > 3400 mg/kg (Rattus) OECD 402	LC50 (4hrs) >13.1 mg/l (Rattus)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	LD50 >2000 mg/kg (Rattus)	>3000 mg/Kg (Rattus)	Ld50 (4h)>5.6mg/L (Rattus)
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	>5000 mg/Kg (Rattus) (OECD 401)	-	>4000 mg/m <sup>3</sup> 4h Vapour (Rattus) (OECD 403)
1,2,4-trimethylbenzene	=3280 mg/kg (Rattus)	> 3160 mg/kg (Oryctolagus cuniculus)	=18 g/m <sup>3</sup> (Rattus) 4 h
Xylenes (o-, m-, p- isomers)	=3500 mg/kg (Rattus)	> 1700 mg/kg (Oryctolagus cuniculus) > 4350 mg/kg (Oryctolagus cuniculus)	= 11 mg/L (ATE)

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Classification based on data available for ingredients. Causes mild skin irritation.

**Serious eye damage/eye irritation** Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** May cause drowsiness or dizziness.

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure.

**Aspiration hazard** May be fatal if swallowed and enters airways.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

# SAFETY DATA SHEET

**CEMENTONE WATERSEAL**  
**Supersedes date** 16-May-2023

**Revision date** 08-Jan-2025  
**Revision Number** 2

**Other adverse effects** No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) RR-91855-8	EL50 (72h) = 4.1 mg/l (Pseudokirchnerella subcapitata) OECD 401	LL50 96hr 10-30 mg/l (Oncorhynchus mykiss)	-	EL50 48hr 10-30mg/l (daphnia magna)		
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics RR-100224-0	-	LC50 (96h) >1000 mg/L Oncorhynchus mykiss	-	LL50 (48h) >1000 mg/L Daphnia magna		
1,2,4-trimethylbenzene 95-63-6	-	LC50: 7.19 - 8.28mg/L (96h, Pimephales promelas)	-	EC50: =6.14mg/L (48h, Daphnia magna)		
Xylenes (o-, m-, p- isomers) 1330-20-7	-	LC50 96 h 2.6 mg/L (Oncorhynchus mykiss ) (OECD 203)	EC50 = 0.0084 mg/L 24 h	EC50 48 h = 3.4 mg/L (Daphnia magna)		
Octane and isomers UNKNOWN	-	-	-	-	1	1

### 12.2. Persistence and degradability

**Persistence and degradability** No information available.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)			
Method	Exposure time	Value	Results
	28 days	biodegradation	74.7 % Readily biodegradable

Xylenes (o-, m-, p- isomers) (1330-20-7)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	biodegradation	87.8 % Readily biodegradable

### 12.3. Bioaccumulative potential

**Bioaccumulation**

#### Component Information

Chemical name	Partition coefficient
1,2,4-trimethylbenzene	3.63
Xylenes (o-, m-, p- isomers)	3.15

### 12.4. Mobility in soil

**Mobility in soil** No information available.

### 12.5. Results of PBT and vPvB assessment

# SAFETY DATA SHEET

CEMENTONE WATERSEAL  
Supersedes date 16-May-2023

Revision date 08-Jan-2025  
Revision Number 2

**PBT and vPvB assessment** The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	The substance is not PBT / vPvB
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	The substance is not PBT / vPvB
1,2,4-trimethylbenzene	The substance is not PBT / vPvB
Xylenes (o-, m-, p- isomers)	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

## 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Waste from residues/unused products** Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

**Other information** Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

### Land transport (ADR/RID)

14.1 UN number or ID number UN1263  
14.2 UN proper shipping name Paint  
14.3 Transport hazard class(es) 3  
Labels 3  
14.4 Packing group III  
Description UN1263, Paint, 3, III, (E), Environmentally Hazardous  
14.5 Environmental hazards Yes  
14.6 Special precautions for user  
Special Provisions 163, 367, 650  
Classification code F1  
Tunnel restriction code (E)  
Limited quantity (LQ) 5 L

### IMDG

14.1 UN number or ID number UN1263  
14.2 UN proper shipping name Paint  
14.3 Transport hazard class(es) 3  
14.4 Packing group I  
Description UN1263, Paint, 3, I, (38°C c.c.), Marine pollutant  
14.5 Marine pollutant P  
14.6 Special precautions for user  
Special Provisions 163, 367  
Limited Quantity (LQ) 500 mL

# SAFETY DATA SHEET

CEMENTONE WATERSEAL  
Supersedes date 16-May-2023

Revision date 08-Jan-2025  
Revision Number 2

EmS-No. F-E, S-E

14.7 Maritime transport in bulk  
according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

## Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN1263
14.2 UN proper shipping name	Paint
14.3 Transport hazard class(es)	3
14.4 Packing group	I
Description	UN1263, Paint, 3, I
14.5 Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	A3, A72, A192
Limited quantity (LQ)	Forbidden
ERG Code	3L

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

##### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

##### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

##### Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

##### Dangerous substance category per Seveso Directive (2012/18/EU)

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

##### Ozone-depleting substances (ODS) Regulation (EU) 2024/590

Not applicable

# SAFETY DATA SHEET

**CEMENTONE WATERSEAL**  
**Supercedes date** 16-May-2023

**Revision date** 08-Jan-2025  
**Revision Number** 2

**Persistent Organic Pollutants**  
Not applicable

**REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors**  
Not applicable

## National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### **Full text of any hazard and/or precautionary statements referred to under Sections 2-15**

H225 - Highly flammable liquid and vapour  
H226 - Flammable liquid and vapour  
H304 - May be fatal if swallowed and enters airways  
H312 - Harmful in contact with skin  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H335 - May cause respiratory irritation  
H336 - May cause drowsiness or dizziness  
H372 - Causes damage to organs through prolonged or repeated exposure  
H373 - May cause damage to organs through prolonged or repeated exposure  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects  
H411 - Toxic to aquatic life with long lasting effects  
H412 - Harmful to aquatic life with long lasting effects

#### **Notes relating to the identification, classification and labelling of substances**

Note C - Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

#### **Legend SECTION 8: Exposure controls/personal protection**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	Sk*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method

# SAFETY DATA SHEET

**CEMENTONE WATERSEAL**  
**Supersedes date** 16-May-2023

**Revision date** 08-Jan-2025  
**Revision Number** 2

Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Chronic aquatic toxicity	Calculation method
Acute aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

## Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)  
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA\_RAC)  
European Chemicals Agency (ECHA) (ECHA\_API)  
Environmental Protection Agency  
Acute Exposure Guideline Level(s) (AEGL(s))  
International Uniform Chemical Information Database (IUCLID)  
National Institute of Technology and Evaluation (NITE)  
NIOSH (National Institute for Occupational Safety and Health)  
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications  
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme  
Organisation for Economic Co-operation and Development Screening Information Data Set

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 08-Jan-2025

**Revision Note** SDS sections updated 9 14

**Training Advice** No information available

**Further information** No information available

## Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878, and Regulation (EC) No. 1272/2008

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**