

Sealocrete All Purpose Fungicidal Silicone Sealant

MOISTURE CURING ACETOXY SILICONE SEALANT

Date: 06/02/2020

Fact Sheet No.: TDS00272

YOUR SMART ADVANTAGES		Storage/Shelf Life	Store for up to 24 months from date of manufacture when stored in original, unopened packaging under dry conditions within the temperature range of +5°C to +25°C. Protect from frost.		
USES			TYPICAL PERFORMANCE DATA (Approx.)		
– Superior adhesion and gap filling properties	– Contains fungicide	Application Temperature	+5°C to +25°C		
– Excellent durability and waterproofing properties		Service Temperature	-40°C to +100°C		
		Coverage	Approx. 15 linear metres of 5mm diameter bead per C20 cartridge		
		Drying Times	Skin Formation: 10 to 20 minutes dependent upon ambient conditions. Through Dry: 2 - 3 mm per 24 hours at 23°C and 50% relative humidity. Always tool sealant within 10 minutes of application.		
		Light Stability	Excellent		
		Slump Resistance	Non slump up to 20mm x 20mm		
		Joint Movement Capability	± 15%		
		Shore A Hardness	20 - 25		
PRODUCT CHARACTERISTICS					
Colours	Black, brown, transparent & white				
Form	Gunnable paste				
Specific Gravity	0.93 approx.				
Composition	Acetoxy cure silicone				
Odour	Pungent, vinegar like smell				
Product Codes	30613759	Black	C20 x 12		
	30613760	Brown	C20 x 12		
	30613951	Transparent	C20 x 12		
	30613761	White	C20 x 12		
DIRECTIONS FOR USE					
IMPORTANT: Before using Sealocrete All Purpose Fungicidal Silicone Sealant refer to the relevant Health & Safety Data Sheet, available at www.bostik.co.uk .					

PREPARATION

1. Ensure all surfaces are clean, dry, firm and free from dust, dirt, oil, grease or other foreign matter.
2. Friable surfaces must be cleaned and degreased.
3. Areas beside a joint should be masked with tape for a neat finish and removed immediately after tooling.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



APPLICATION

4. Cut the dome of the cartridge with a sharp knife, taking care not to damage the thread, pierce the foil membrane, then screw the nozzle on and insert into a cartridge gun.
5. Extrude sealant into the joint ensuring complete contact with both surfaces.
6. Smooth the sealant with a knife within 5 minutes of application.
7. The width of the joint should not be less than 4 times the anticipated movement and have a minimum depth of 3mm.

CLEANING

Uncured Sealant:

8. The excess uncured sealant should be removed carefully using a soft scraper. The remainder can be removed using a cloth just moistened with white spirit. Repeat using another clean cloth moistened with white spirit.

Cured Sealant:

9. There is no adequate solvent; carefully cut away excess with a very sharp knife. Do not use solvent to remove product from skin – use soap and water.

PRECAUTIONS IN USE

Sealocrete All Purpose Fungicidal Silicone Sealant is not suitable for sealing double-glazing units. Avoid using with self-cleaning glass. Do not use against bitumen containing materials. Cannot be over-painted. Do not use on or near bitumen.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.co.uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Sealocrete All Purpose Fungicidal Silicone Sealant, available at www.bostik.co.uk.

**CONSTRUCTION PRODUCT REGULATION
DECLARATION OF PERFORMANCE**

No: TDS00272

Product Description: **Sealocrete All Purpose Silicone Sealant**

Product Code: **5011961873058, 5011961873041, 5011961873027, 5011961873195**

Intended Use: **All Purpose Silicone Sealant**

Manufacturer: **Bostik Ltd**
Contact Address: **Common Road
Stafford
ST16 3EH**

System of Assessment: **System 3**

Harmonised Standard: **BS EN 15651-1,2,3:2012**

Notified Body: **0074**

Declared Performance:

Essential Characteristics	Performance	Harmonised technical specification
Reaction to Fire	F	
Release of Chemicals	None	See Safety Data Sheet

Water Tightness & Air Tightness as determined by:

Resistance to Flow	≤3mm	BS EN 15651-1,2,3:2012
Loss of Volume	NPD	
Elastic Recovery	NPD	BS EN 15651-1,2:2012
Tensile properties after immersion in water at 23°C*	≥25%	BS EN 15651-1,3:2012
Tensile properties at maintained extension after immersion in water at 23°C*	NF	BS EN 15651-1,2,3:2012
Microbiological Growth	NPD	BS EN 15651-3:2012
Durability	NPD	BS EN 15651-1,2,3:2012

***Conditioning method A, tested on Aluminium Substrate, no primer**

The performance of the product Sealocrete All Purpose Silicone Sealant 5011961873058, 5011961873041, 5011961873027, 5011961873195 is in conformity with the declared performance shown in the table above.

This declaration of performance is issued under the sole responsibility of Bostik Ltd.

Signed for and on behalf of Bostik Ltd by:

Name: Alison Jamieson

Function: S.H.E.Q. Manager

Signature: 

Date: May 2014

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDSs, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	sds.box-eu@bostik.com