



Certificate number: 2403726 (1)

Issued 19/03/2024

Expires 19/03/2029

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

Methven UK Limited.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

CERTIFICATE

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Methven UK Limited
3-3a Stone Cross Court
Yew Tree Way
Golborne
Warrington
WA3 3JD



KUKreg4

Product Certificate

Appendix to Certificate number: 2403726

The following products belong to this certificate

<p>PRODUCT DESCRIPTION Range of basin mixers with brass bodies and various finishes. Fitted with ceramic cartridge headworks. ATS3 – Without Production Surveillance.</p>
<p>MODEL(S) AMBCPUK Amio Basin Mixer AMBBK Amio Basin Mixer - Matte Black AMBMCPUK Amio Mini Basin Mixer AMBMBK Amio Mini Basin Mixer - Matte Black AMTBCPUK Amio Tall Basin Mixer AMTBK Amio Tall Basin Mixer - Matte Black</p>
<p>SIZE: ½" captive nut.</p>
<p>SCOPE: Manufacturer recommended maximum working pressure 5 Bar & maximum operating temperature 60°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 60°C.</p>
<p>MARKING Methven on operating member. DTC53 on body.</p>
<p>MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.</p>
<p>BACKFLOW PROTECTION NOTES If this tap or combination tap is installed so that its base is no lower than the spillover level of the receiving vessel a Type AUK3 air gap is achieved. Consider balanced supplies or appropriate backflow protection at the inlets.</p>
<p>ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.</p>

Extra Notes