

Hexo Blocks

Hexo offers a striking alternative to traditional square or rectangular paving formats. Its unique shape and granite - textured finish deliver a bold, modern aesthetic - providing a distinctive design statement that sets it apart from standard paving options.



Pedestrian
Use



Light
Traffic



Slip
Resistance



Factory Sealed
Available

Colour Profile



Silver Granite



Black Granite

3D Profile



Features


- High - performance concrete block paving, designed for visual impact and versatility
- Lightly textured surface with premium granite aggregates for enhanced aesthetics and durability
- Supplied in a 60mm depth, suitable for both pedestrian and vehicular applications
- A striking alternative to traditional square or rectangular paving formats
- Available in two standard colours, with bespoke colour options available on request
- Half - hexagon units available to assist with edge detailing and the squaring - off of layouts

Benefits

- Highly durable, with increased cement content and a robust granite surface for long - lasting performance
- Maintains exceptionally low slip resistance throughout its lifecycle - outperforming natural granite and porcelain alternatives
- Offers significant savings on both supply and installation when compared to natural stone solutions
- Factory - applied sealant available on request, enhancing protection and reducing maintenance needs.



Sizing



200 x 230

Packaging Information

Dimensions (mm)	Colours	Pcs per m ²	m ² per Bale	Pcs per Bale	Pcs per Layer	No of Layers	Approx Bale Weight (kg)	Profile
200x230x60	Silver Granite, Black Granite	29	7.5	230	23	N/A	960	Chamfer

Full bale consists of 210 full pieces and 20 half blocks

Technical Performance and Data

Product Type	Concrete Block Paving
Product Standard	EN 1338:2003
Manufacturing Method	Hydraulically pressed semi - dry concrete
Finish	Textured Granite Aggregate Finish
Packaging Information	Baled, strapped and plastic cover
Slip/Skid Resistance	Extremely low - Typically USRV / PTV > 75
Strength	Typically tensile splitting strength of > 3.6 MPa and a failure load of > 250N/ mm
Application & Trafficking	Product suitable for both pedestrian, vehicular traffic when installation in conjunction with the correct, site specific sub - base design.
Joint	Hexo Block Paving have a 1.5mm approx. internal spacer nib which will give a resulting standard joint width of approx. 2mm when laid. Joints should be filled with kiln dried sand. Note that silver granite kiln dried sand must be used for the silver colour option to reduce potential staining
BREEAM	A rated in accordance with Green Guide Specification Edition 4, 2009. A+ rated when used in conjunction with a prepared recycled sub - base.

Get In Touch:

(01) 801 3484

techsupport@kilsaran.ie

