



Plasterer's Grit

ONE COAT PLASTER BONDING AGENT

TECHNICAL SHEET NO: TDS02252 28/06/2024

SMART ADVANTAGES

- Ready-to-use - no mixing required
- No mess - easy-to-apply with roller or brush
- Even, mechanical key for plaster

DESCRIPTION

Bostik Plasterer's Grit has been specially developed for the plastering professional. Previously called Plasterer's Stabilising Primer, it primes and stabilises most interior surfaces to give extra grip prior to the application of new plaster.

It's perfect for re-skimming and can be applied straight from the bucket onto previously plastered walls, internal render or concrete. The grit suspended in the product provides an excellent mechanical key.

Bostik Plasterer's Grit is coloured green to show uniform coverage and only one coat is required using a short pile roller or soft brush to provide an even key for plaster. It gives a more uniform surface that dries evenly, providing excellent adhesion and a faster, easier finish. It reduces suction on porous surfaces, allowing a consistent plastering working time and reducing the risk of cracking.

Unlike other plaster bonding agents, there's no mixing required before use and an evenly distributed key is achieved when applied to the wall, which provides a much-improved substrate for plastering.



TECHNICAL CHARACTERISTICS

Colour	Green
Form	Viscous liquid
Composition	Water-based polymers & additives
Application temperature	Above +5°C
Specific gravity	1.43 approx.
Drying time	Up to 24 hours approx. (depending on ambient conditions)

COVERAGE

- 3m² to 4m² per litre (depending on the porosity and texture of the surface being prepared)

APPLICATION

IMPORTANT: Before using Bostik Plasterer's Grit, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

- Surfaces must be dry, clean, sound and free from grease, dust or loose material. Mechanically remove any loose or flaking material. Any existing paint should be checked for soundness and adhesion. Do not apply over wallpaper or textured ceilings. Protect adjacent surfaces from splashes.
- Ensure that any surface to be plastered is strong enough to support the weight of the new plaster.
- Bostik Plasterer's Grit will not make up for defective surfaces and the bond will only be as good as the weakest part of the system i.e., when applied to paint. Bostik is not responsible for failure of an underlying substrate.
- Tape over any obvious joints or cracks with plasterer's scrim tape.
- Any chalky or high suction surfaces should be treated with a 1 : 1 dilution of Bostik SBR with clean water, which can be applied by brush or roller. Allow to dry completely before applying Bostik Plasterer's Grit.

APPLICATION

- Bostik Plasterer's Grit is primarily designed to provide a consistent, even background with improved adhesion for the application of new plaster. For specific applications please contact Bostik Technical Services.
- Apply Bostik Plasterer's Grit straight from the bucket with a short pile roller or soft brush, to give an even texture over the entire surface. Only one coat is required. Do not dilute.
- Allow to dry completely before applying plaster (up to 24 hours). Drying times are dependent on the porosity of the surface and ambient conditions.
- Once dry, apply first tight coat of plaster, followed by a second coat of plaster approx. 2mm to 3mm in thickness. Finish as normal.

CLEANING

- Clean tools and equipment with water immediately after use. Remove any splashes as dried product is difficult to remove.

STORAGE

- Store and transport securely in an upright position. Ensure the lid is secure. Store for up to 12 months from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +5°C to +25°C and out of direct sunlight. Protect from frost.

PRECAUTIONS IN USE

For internal use only. Not suitable for priming prior to adhesive fixing of plasterboards, or for use with dot and dab applications. Do not apply to plasterboard or use in areas subject to constant damp. For glossy surfaces such as ceramic tiles, external use, application of renders or very high absorbency backgrounds, use Bostik Renderer's Grit.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Plasterer's Grit, available at www.bostik.com/uk.

PACKAGING

Product codes	30624682	5L bucket
	30625351	10L bucket

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top left-hand corner on the front of this document.

Sales	Tel: 0844 371 1192	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	sds.box-eu@bostik.com

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

Bostik Ltd
Common Road,
Stafford, ST16 3EH, UK
Phone: +44 (0)1785 272625
www.bostik.com/uk

BOSTIK HOTLINE

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.