



Super Glue Liquid

CYANOACRYLATE ADHESIVE IN A TUBE

TECHNICAL SHEET NO: TDS00484 04/01/2024

SMART ADVANTAGES

- Ultra strong
- Fast setting – Bonds in seconds
- Fine nozzle

DESCRIPTION

Bostik Super Glue Liquid is a high strength, fast setting solvent free adhesive which can be used for virtually any type of fastening job and bonds in seconds without the need for heat or clamps.

Bostik Super Glue Liquid has been formulated to achieve the strongest possible bond between non-porous materials such as wood, rubber, metal, ceramics, hard plastics, leather and much more.



TECHNICAL CHARACTERISTICS

Colour	Clear
Form	Thin liquid
Composition	Ethyl Cyanoacrylate
Specific gravity	1.1 approx.
Setting Times	Instant bond for most materials. Maximum strength is achieved in 24 to 48 hours.
Working Temperature	-55°C to +80°C.

APPLICATION

IMPORTANT: Before using Bostik Super Glue Liquid refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

- Read all instructions carefully before use.
- Work on a protected surface as any spillages are very difficult to remove, particularly from sensitive surfaces like fabrics and skin.
- Make sure all surfaces to be bonded are clean and dry, being free from dirt and grease.
- Always position the tube away from you when opening and don't squeeze.

APPLICATION

- When using Bostik Super Glue Liquid for the first time, screw down the cap and nozzle tightly to pierce the tube. Remove the cap to commence application.
- Avoiding skin contact, apply a small amount of glue to one surface, press the surfaces together and hold for a few seconds until the glue sets.
- After use, wipe the nozzle with a cloth (avoiding skin contact) and replace the cap.
- Store tube upright in a cool, dark place.

CLEANING

- Bostik Super Glue Liquid has good resistance to most oils and solvents and can be very difficult to remove.
- Bostik Super Glue Liquid bonds to skin very quickly and easily. Should this happen, please do not panic. Do not attempt to pull apart as this may damage the skin. If left the bond will loosen within 60 minutes without doing anything. Hot soapy water and gentle peeling will part the bond, this can take 10 minutes.
- Acetone will very slowly soften set super glue. Before attempting to use, check that it is safe to use a highly flammable solvent and that the surfaces to which the super glue is adhered are not damaged by the solvent. Do not use acetone or solvents on the skin.
- Always test before using any solvent.

STORAGE

- Store for up to 12 months from date of manufacture when stored in the original, unopened packaging in a cool, dry place 20-25°C. For long-term storage, refrigeration (5°C) is recommended.

PRECAUTIONS IN USE

Protect work surface. Product won't work on soft plastics like polythene or absorbent surfaces like paper. Don't use for objects that hold hot foods/liquids or high stress joints.

For any application not covered please contact Technical Services on +44 (0)1785 272625, or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for Bostik Super Glue Liquid, available at www.bostik.com/uk.

PACKAGING

Product codes	30813340	3g tube on blister x 12
---------------	----------	-------------------------

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	sds.box-eu@bostik.com

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

Bostik Ltd
Common Road,
Stafford, ST16 3EH, UK
Phone: +44 (0)1785 272625
www.bostik.com/uk

BOSTIK HOTLINE

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.