

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

CEMENTONE PAVESEAL Revision Date: 25-Sep-2020 Supercedes Date: 24-Jun-2019

Revision Number 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

CEMENTONE PAVESEAL **Product Name**

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Primers, Sealers, and Undercoaters. Recommended use

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

SDS.box-EU@bostik.com E-mail address

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650

Ireland +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aspiration hazard	Category 1 - (H304)
Specific target organ toxicity (single exposure)	Category 3 - (H335,H336)
Chronic aquatic toxicity	Category 2 - (H411)
Flammable liquids	Category 2 - (H225)

2.2. Label Elements

Contains: Hydrocarbons, C9, aromatics, 1,3,5-Trimethylbenzene



Signal word DANGER

Hazard statements

H304 - May be fatal if swallowed and enters airways.

H335 - May cause respiratory irritation.

Supercedes Date: 24-Jun-2019 Revision Number 4

H336 - May cause drowsiness or dizziness.

H411 - Toxic to aquatic life with long lasting effects.

H225 - Highly flammable liquid and vapour.

EU Specific Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking.

EUH208 - Contains Methyl methacrylate & Butyl methacrylate. May produce an allergic reaction.

Precautionary statements

CEMENTONE PAVESEAL

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 - Avoid breathing vapours/spray.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves and eye/face protection.

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331 - Do NOT induce vomiting.

P391 - Collect spillage.

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

P501 - Dispose of contents/ container to an approved waste disposal plant.

Additional information

This product requires tactile warnings if supplied to the general public. This product requires child resistant fastenings if supplied to the general public.

2.3. Other Hazards

No information available

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT) This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB)

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Hydrocarbons, C9, aromatics	918-668-5	64742-95-6	80 - 100	Flam. Liq. 3 (H226) STOT SE 3 (H335) STOT SE 3 (H336) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) (EUH066)		01-2119455851- 35-XXXX
1,3,5-Trimethylbenzene	203-604-4	108-67-8	1- <2.5	STOT SE 3 (H335) Aquatic Chronic	STOT SE 3 :: C>=25%	01-2119463878- 19-XXXX

Revision Date: 25-Sep-2020

CEMENTONE PAVESEAL
Supercedes Date: 24-Jun-2019
Revision Date: 25-Sep-2020
Revision Number 4

2 (H411) Flam. Liq. 3 (H226) Methyl methacrylate 201-297-1 80-62-6 0.1 - <1 Skin Irrit. 2 STOT SE 3 :: 01-2119452498-(H315) C > = 10%28-xxxx Skin Sens. 1B (H317)STOT SE 3 (H335)Flam. Liq. 2 (H225)Butyl methacrylate 202-615-1 97-88-1 0.1 - <1 STOT SE 3 :: 01-2119486394-Skin Irrit. 2 (H315)C>=10% 28-XXXX Eye Irrit. 2 (H319) Skin Sens. 1B (H317)STOT SE 3 (H335) Flam. Liq. 3 (H226)

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Inhalation Aspiration into lungs can produce severe lung damage. If breathing has stopped, give

artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention.

Delayed pulmonary edema may occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Keep eye wide open while rinsing. Do not rub affected area.

Skin contactWash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes.

Ingestion Aspiration hazard if swallowed - can enter lungs and cause damage. Do NOT induce

vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Clean mouth with water and drink afterwards plenty of water. Never give anything by

mouth to an unconscious person. Get immediate medical advice/attention.

Self-protection of the first aider Remove all sources of ignition. See section 8 for more information. Ensure that medical

personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give

mouth-to-mouth resuscitation. Use personal protective equipment as required.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Inhalation of high vapour

Supercedes Date: 24-Jun-2019 Revision Number 4

concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

Revision Date: 25-Sep-2020

vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Because of the danger of aspiration, emesis or gastric lavage should not be used unless

the risk is justified by the presence of additional toxic substances.

SECTION 5: Firefighting measures

5.1. Extinguishing media

CEMENTONE PAVESEAL

Suitable extinguishing media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions See section 8 for more information. Avoid contact with skin, eyes or clothing. Keep

people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking,

flares, sparks or flames in immediate area). Pay attention to flashback. Take

precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Evacuate

personnel to safe areas. Ensure adequate ventilation. Use personal protective

equipment as required.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or

spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A

vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later

disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Eliminate all ignition sources if safe to do so.

6.4. Reference to other sections

CEMENTONE PAVESEAL
Supercedes Date: 24-Jun-2019
Revision Date: 25-Sep-2020
Revision Number 4

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapours or mists. In case of insufficient ventilation, wear

suitable respiratory equipment.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should

not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights,

electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Keep containers tightly closed in a dry, cool and well-ventilated place. Store

locked up. Keep out of the reach of children. Store away from other materials.

7.3. Specific end use(s)

Specific Use(s)

Primers, Sealers, and Undercoaters.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
1,3,5-Trimethylbenzene	TWA: 20 ppm	TWA: 20 ppm	-
108-67-8	TWA: 100 mg/m ³	TWA: 100 mg/m ³	
		STEL: 60 ppm	
		STEL: 300 mg/m ³	
Methyl methacrylate	TWA: 50 ppm	TWA: 50 ppm	TWA: 50 ppm
80-62-6	STEL: 100 ppm	STEL: 100 ppm	TWA: 208 mg/m ³
			STEL: 100 ppm
			STEL: 416 mg/m ³

Derived No Effect Level (DNEL) No information available

Supercedes Date: 24-Jun-2019 Revision Number 4

Predicted No Effect Concentration No information available.

(PNEC)

8.2. Exposure controls

CEMENTONE PAVESEAL

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be

exhausted directly at the point of origin.

Personal Protective Equipment

Eye/face protection Tight sealing safety goggles. Face protection shield. Eye protection must conform to

standard EN 166.

Hand protection Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the

breakthrough time of the glove material is not exceeded. Refer to glove supplier for

Revision Date: 25-Sep-2020

information on breakthrough time for specific gloves.

Skin and body protection Antistatic footwear. Wear fire/flame resistant/retardant clothing. Suitable protective

clothing.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Liquid
Colour Clear
Odour Solvent

Odour threshold No information available

Property Values Remarks • Method

pH No data availableMelting point / freezing point No data available

Evaporation rate No data available Flammability (solid, gas) Not applicable for liquids .

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapour pressureNo data availableVapour densityNo data available

Relative density 0.9

Water solubility No data available Solubility(ies) No data available Partition coefficient No data available **Autoignition temperature** No data available No data available **Decomposition temperature** Kinematic viscosity No data available No data available **Dynamic viscosity Explosive properties** No data available **Oxidising properties** No data available

9.2. Other information

Solid content (%)

VOC Content (%)

Density

No information available

No information available

No information available

SECTION 10: Stability and reactivity

CEMENTONE PAVESEAL
Supercedes Date: 24-Jun-2019
Revision Date: 25-Sep-2020
Revision Number 4

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical

None.

impact

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materialsNone known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information .

Inhalation Aspiration into lungs can produce severe lung damage. May cause pulmonary edema.

Pulmonary edema can be fatal. May cause drowsiness or dizziness. Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. May cause irritation.

Skin contact Repeated exposure may cause skin dryness or cracking.

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if

swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary

edema and pneumonitis. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Inhalation of high vapour

concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting.

Numerical measures of toxicity

Acute toxicity

CEMENTONE PAVESEAL
Supercedes Date: 24-Jun-2019
Revision Date: 25-Sep-2020
Revision Number 4

The following values are calculated based on chapter 3.1 of the GHS document ATEmix (inhalation-dust/mist) 154.30 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C9, aromatics	LD50 =3492 mg/kg (Rattus)	LD50 > 3160 mg/kg	=3400 ppm (Rattus) 4 h
64742-95-6		(Oryctolagus cuniculus)	
		OECD 402	
1,3,5-Trimethylbenzene	=5000 mg/kg (Rattus)		= 24 g/m³ (Rat) 4 h
108-67-8			
Methyl methacrylate	=7872 mg/kg (Rattus)	5000 - 7500 mg/kg	=7093 ppm (Rattus) 4 h
80-62-6		(Oryctolagus cuniculus) > 5	
		g/kg (Oryctolagus cuniculus)	
Butyl methacrylate	=16 g/kg (Rattus)	= 11300 mg/kg (Oryctolagus	=4910 ppm (Rattus) 4 h
97-88-1		cuniculus)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationBased on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as mutagenic.

Chemical name	European Union
Hydrocarbons, C9, aromatics 64742-95-6	Muta. 1B

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C9,	ErL50 (72h) =	LL50 (96h) = 9.2	-	EL50 (48h) =		, ,

CEMENTONE PAVESEAL
Supercedes Date: 24-Jun-2019
Revision Date: 25-Sep-2020
Revision Number 4

aromatics	2.9 mg/L	mg/L		3.2 mg/L	
64742-95-6	(Pseudokirchner	(Oncorhynchus		(Daphnia	
	iella	mykiss) OECD		magna) OECD	
	subcapitata)	203		202	
	OECD 201	200		202	
1.2.5 Trime of builbon and a		1.050.		F050: 50m m/l	
1,3,5-Trimethylbenzene	-	LC50:	-	EC50: =50mg/L	
108-67-8		=3.48mg/L (96h,		(24h, Daphnia	
		Pimephales		magna)	
		promelas)			
Methyl methacrylate	EC50:	LC50 96 h > 79	-	EC50: =69mg/L	
80-62-6	=170mg/L (96h,	mg/L		(48h, Daphnia	
	Pseudokirchneri	_		magna)	
	ella subcapitata)	, ,		-3 -7	
	ona carcapitata)	Lepomis			
		macrochirus 96h			
D 1 1 1 1 1 1	F050 57 //	=191-283 mg/l	E050 07 //	E050 00 //	
Butyl methacrylate	EC50: =57mg/L		EC50 = 37 mg/L		
97-88-1	(96h,	(96h,	5 min	(48h, Daphnia	
	Pseudokirchneri	Pimephales	EC50 = 49 mg/L	magna)	
	ella subcapitata)	promelas)	15 min		
			EC50 = 55 mg/L		
			30 min		
			EC50 > 253.6		
			mg/L 18 h		
	l .	l .			

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Methyl methacrylate 80-62-6	1.38	•
Butyl methacrylate 97-88-1	2.26	-

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment . The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Hydrocarbons, C9, aromatics	The substance is not PBT / vPvB
64742-95-6	
1,3,5-Trimethylbenzene	The substance is not PBT / vPvB
108-67-8	
Methyl methacrylate	The substance is not PBT / vPvB
80-62-6	PBT assessment does not apply
Butyl methacrylate	The substance is not PBT / vPvB
97-88-1	PBT assessment does not apply

12.6. Other adverse effects

CEMENTONE PAVESEAL
Supercedes Date: 24-Jun-2019
Revision Date: 25-Sep-2020
Revision Number 4

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or

weld containers.

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Note: The shipping descriptions shown here are for bulk shipments only, and may not apply to

shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

Land transport (ADR/RID)

14.1 UN number UN1263

14.2 Proper Shipping Name Paint related material, Environmentally Hazardous

14.3 Transport hazard class(es) 3 Labels 3 14.4 Packing group ||

Description UN1263, Paint related material, 3, II, (D/E), Environmentally Hazardous

14.5 Environmental hazards Yes

14.6 Special Provisions 163, 640D, 650, 367

Classification code F1
Tunnel restriction code (D/E)
Limited Quantity (LQ) 5 L
ADR Hazard Id (Kemmler 33

Number)

<u>IMDG</u>

14.1 UN number UN1263

14.2 Proper Shipping Name Paint related material (Hydrocarbons, C9, aromatics), Marine Pollutant

14.3 Transport hazard class(es)14.4 Packing group

Description UN1263, Paint related material (Hydrocarbons, C9, aromatics), 3, II, (-40°C c.c.),

Marine Pollutant

 14.5 Marine pollutant
 P.

 14.6 Special Provisions
 163, 367

 Limited Quantity (LQ)
 5 L

 EmS-No
 F-E, S-E

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number UN1263

14.2 Proper Shipping Name Paint related material

14.3 Transport hazard class(es) 3
14.4 Packing group

Description UN1263, Paint related material, 3, II

14.5 Environmental hazards Yes

14.6 Special Provisions A3, A72, A192

Limited Quantity (LQ) 1 L

CEMENTONE PAVESEALRevision Date: 25-Sep-2020Supercedes Date: 24-Jun-2019Revision Number 4

ERG Code 3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Hydrocarbons, C9, aromatics	64742-95-6	

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS P5b - FLAMMABLE LIQUIDS P5c - FLAMMABLE LIQUIDS E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

Supercedes Date: 24-Jun-2019 Revision Number 4

EUH066 - Repeated exposure may cause skin dryness or cracking

H225 - Highly flammable liquid and vapour H226 - Flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

CEMENTONE PAVESEAL

H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness

H411 - Toxic to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision Date: 25-Sep-2020

Indication of changes

Revision note SDS sections updated, 3, 14.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Revision Date: 25-Sep-2020