

EVO-STIK RESIN-W POLYURETHANE WOOD ADHESIVE
 Supersedes Date: 16-Nov-2017

Revision date 07-Oct-2019
Revision Number 1.02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name EVO-STIK RESIN-W POLYURETHANE WOOD ADHESIVE
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited
 Common Rd
 ST16 3EH
 Stafford UK
 Tel: +44 (1785) 27 26 25
 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone
United Kingdom +44 (1785) 272650
Ireland +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Respiratory sensitisation	Category 1 - (H334)
Skin sensitisation	Category 1 - (H317)
Carcinogenicity	Category 2 - (H351)
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Specific target organ toxicity — repeated exposure	Category 2 - (H373)

2.2. Label Elements

Contains: 4,4'-Methylenediphenyl diisocyanate



Signal word

SAFETY DATA SHEET

EVO-STIK RESIN-W POLYURETHANE WOOD ADHESIVE
Supersedes Date: 16-Nov-2017

Revision date 07-Oct-2019
Revision Number 1.02

DANGER

Hazard statements

H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335 - May cause respiratory irritation
H351 - Suspected of causing cancer
H373 - May cause damage to organs through prolonged or repeated exposure

EU Specific Hazard Statements

EUH204 - Contains isocyanates. May produce an allergic reaction

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P201 - Obtain special instructions before use
P260 - Do not breathe mist/vapours/spray
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves and eye/face protection
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap
P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor
P405 - Store locked up
P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product requires tactile warnings if supplied to the general public.

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. Type A1 according to standard EN 14387) is used.

2.3. Other Hazards

No information available

PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2. Mixtures

Chemical name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
4,4'-Methylenediphenyl diisocyanate	202-966-0	101-68-8	40 - <80	Acute Tox. 4 (H332) Skin Irrit. 2 (H315)	STOT SE 3 :: C>=5% Skin Irrit. 2 :: C>=5% Eye Irrit. 2 :: C>=5% Resp. Sens. 1 ::	01-2119457014-47-XXXX

SAFETY DATA SHEET

EVO-STIK RESIN-W POLYURETHANE WOOD ADHESIVE
 Supersedes Date: 16-Nov-2017

Revision date 07-Oct-2019
 Revision Number 1.02

				Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351) STOT SE 3 (H335) STOT RE 2 (H373)	C>=0.1%	
Morpholine, 4,4'-(oxydi-2,1-ethanediy l)bis-	229-194-7	6425-39-4	1 - <5	Eye Irrit. 2 (H319)		01-2119969278- 20-XXXX

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.
Inhalation	May cause allergic respiratory reaction. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Get immediate medical advice/attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes.
Ingestion	May produce an allergic reaction. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention. Clean mouth with water. Drink 1 or 2 glasses of water.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. See section 8 for more information. Avoid breathing vapours or mists.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/or wheezing. Itching. Rashes. Hives. Burning sensation. Difficulty in breathing.
-----------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	May cause sensitisation in susceptible persons. Treat symptomatically.
------------------------	--

SAFETY DATA SHEET

EVO-STIK RESIN-W POLYURETHANE WOOD ADHESIVE
Supersedes Date: 16-Nov-2017

Revision date 07-Oct-2019
Revision Number 1.02

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Foam. Carbon dioxide (CO₂). Dry chemical. Water spray or fog.

Unsuitable extinguishing media Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Product is or contains a sensitiser. May cause sensitisation by inhalation and skin contact. May cause sensitisation by skin contact.

Hazardous combustion products Carbon oxides. Nitrogen oxides (NO_x).

5.3. Advice for firefighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment. Move containers from fire area if you can do it without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid breathing vapours or mists.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Provide extract ventilation to points where emissions occur. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash it before reuse. Avoid breathing vapours or mists.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Remove and wash contaminated

SAFETY DATA SHEET

EVO-STIK RESIN-W POLYURETHANE WOOD ADHESIVE
Supersedes Date: 16-Nov-2017

Revision date 07-Oct-2019
Revision Number 1.02

clothing and gloves, including the inside, before re-use. Wash hands before breaks and immediately after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

7.3. Specific end use(s)

Specific Use(s)
Adhesives.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
4,4'-Methylenediphenyl diisocyanate 101-68-8	-	TWA: 0.005 ppm TWA: 0.02 mg/m ³ STEL: 0.015 ppm STEL: 0.07 mg/m ³	TWA: 0.02 mg/m ³ STEL: 0.07 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)

4,4'-Methylenediphenyl diisocyanate (101-68-8)

Type	worker Short term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	50 mg/kg bw/d

Type	worker Short term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	0.1 mg/m ³

Type	worker Short term Local health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	28700 µg/cm ²

Type	worker Short term Local health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	0.1 mg/m ³

Type	worker Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	0.05 mg/m ³

Type	worker Long term Local health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	0.05 mg/m ³

SAFETY DATA SHEET

EVO-STIK RESIN-W POLYURETHANE WOOD ADHESIVE
 Supersedes Date: 16-Nov-2017

Revision date 07-Oct-2019
 Revision Number 1.02

Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis- (6425-39-4)	
Type	Long term Systemic health effects worker
Exposure route	Inhalation
Derived No Effect Level (DNEL)	7.28 mg/m ³

Type	Long term Systemic health effects worker
Exposure route	Dermal
Derived No Effect Level (DNEL)	1 mg/kg bw/d

Derived No Effect Level (DNEL)	
4,4'-Methylenediphenyl diisocyanate (101-68-8)	
Type	Consumer Short term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	25 mg/kg bw/d

Type	Consumer Short term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	0.05 mg/m ³

Type	Consumer Short term Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	20 mg/kg bw/d

Type	Consumer Short term Local health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	17200 µg/cm ²

Type	Consumer Short term Local health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	0.05 mg/m ³

Type	Consumer Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	0.025 mg/m ³

Type	Consumer Long term Local health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	0.025 mg/m ³

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
4,4'-Methylenediphenyl diisocyanate (101-68-8)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	1 mg/l
Marine water	0.1 mg/l
Soil	1 mg/kg dry weight
Sewage treatment plant	1 mg/l
Freshwater - intermittent	10 mg/l

Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis- (6425-39-4)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.1 mg/l
Marine water	0.01 mg/l
Freshwater sediment	8.2 mg/kg dry weight
Marine sediment	0.82 mg/kg dry weight
Freshwater - intermittent	1 mg/l
Sewage treatment plant	100 mg/l

SAFETY DATA SHEET

EVO-STIK RESIN-W POLYURETHANE WOOD ADHESIVE
Supersedes Date: 16-Nov-2017

Revision date 07-Oct-2019
Revision Number 1.02

Soil	1.58 mg/kg dry weight
------	-----------------------

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

Personal Protective Equipment

Eye/face protection Tight sealing safety goggles. Wear safety glasses with side shields (or goggles). Face protection shield.

Hand protection Gloves are provided with this product. Wear protective gloves. Council Directive 89/686/EEC: Council Directive 89/686/EEC of 21 December 1989 on the approximation of the laws of the Member States relating to personal protective equipment.

Skin and body protection Suitable protective clothing. Suitable protective clothing.

Respiratory protection Provide adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Recommended filter type: A2/P3.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Gel
Colour Cream
Odour Musty
Odour threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	> 330 °C	
Flash point	> 200 °C	CC (closed cup)
Evaporation rate	approx. No data available	
Flammability (solid, gas)	Not applicable for liquids .	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	0.01	
Vapour density	8.5	
Relative density	1.10	
Water solubility	Insoluble in water Slightly soluble	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	>600 °C	
Decomposition temperature	No data available	
Kinematic viscosity	> 21 mm ² /s	@ 40°C
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

9.2. Other information

Solid content (%) No information available
Softening Point No information available
Molecular weight No information available
VOC Content (%) No information available
Density No information available
Bulk density No information available

SAFETY DATA SHEET

EVO-STIK RESIN-W POLYURETHANE WOOD ADHESIVE
Supersedes Date: 16-Nov-2017

Revision date 07-Oct-2019
Revision Number 1.02

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion Data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Hazardous polymerisation Hazardous polymerisation may occur.

10.4. Conditions to avoid

Conditions to avoid Excessive heat.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Carbon monoxide. Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Thermal decomposition can lead to release of irritating and toxic gases and vapours. Hydrogen cyanide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause sensitisation in susceptible persons. (based on components). May cause irritation of respiratory tract. Harmful by inhalation.

Eye contact Irritating to eyes. Causes serious eye irritation.

Skin contact Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May cause sensitisation by skin contact. Causes skin irritation.

Ingestion Specific test data for the substance or mixture is not available. May cause additional affects as listed under "Inhalation". Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing,

SAFETY DATA SHEET

EVO-STIK RESIN-W POLYURETHANE WOOD ADHESIVE
Supersedes Date: 16-Nov-2017

Revision date 07-Oct-2019
Revision Number 1.02

tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document
ATEmix (inhalation-dust/mist) 3.41 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
4,4'-Methylenediphenyl diisocyanate 101-68-8	=31600 mg/kg (Rattus) = 9200 mg/kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus) OECD 402	=1.5 mg/L (Rattus) 4 h
Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis- 6425-39-4	LD50 =2025 mg/Kg (Rattus)	LD50 >3000 mg/Kg (Oryctolagus cuniculus)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitisation May cause sensitisation by inhalation. May cause sensitisation by skin contact.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Classification based on data available for ingredients. Contains a known or suspected carcinogen.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	European Union
4,4'-Methylenediphenyl diisocyanate 101-68-8	Carc. 2

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

SAFETY DATA SHEET

EVO-STIK RESIN-W POLYURETHANE WOOD ADHESIVE
Supersedes Date: 16-Nov-2017

Revision date 07-Oct-2019
Revision Number 1.02

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to Micro-organisms	Crustacea	M-Factor
4,4'-Methylenediphenyl diisocyanate 101-68-8	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	>1000 mg/l (Danio rerio)	-	EC50 (24H) >1000 mg/L Daphnia magna	-
Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis- 6425-39-4	EC50 (72h) >100 mg/L Algae (Pseudokirchnerella subcapitata) Static	LC50 (96h) >2150 mg/L (Danio rerio) Static	-	EC50 (48h) >100 mg/L (Daphnia magna) Static	-

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information			
4,4'-Methylenediphenyl diisocyanate (101-68-8)			
Method	Exposure time	Value	Results
OECD Test No. 302C: Inherent Biodegradability: Modified MITI Test (II)	28 days	0% biodegradation	Not readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
4,4'-Methylenediphenyl diisocyanate 101-68-8	4.51	200
Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis- 6425-39-4	0.5	3

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Chemical name	PBT and vPvB assessment
4,4'-Methylenediphenyl diisocyanate 101-68-8	The substance is not PBT / vPvB
Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis- 6425-39-4	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

SAFETY DATA SHEET

EVO-STIK RESIN-W POLYURETHANE WOOD ADHESIVE
Supersedes Date: 16-Nov-2017

Revision date 07-Oct-2019
Revision Number 1.02

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Do not reuse empty containers. Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	07 02 08 other still bottoms and reaction residues 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances 15 01 10*: Packaging containing residues of or contaminated by dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN Number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing Group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

IMDG

14.1 UN number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine Pollutant	Np
14.6 Special Provisions	None
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

SAFETY DATA SHEET

EVO-STIK RESIN-W POLYURETHANE WOOD ADHESIVE
Supersedes Date: 16-Nov-2017

Revision date 07-Oct-2019
Revision Number 1.02

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
4,4'-Methylenediphenyl diisocyanate	101-68-8	56[a].

56 . If product supplied to the general public with substance $\geq 0.1\%$, then gloves must be provided with the product.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National Regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335 - May cause respiratory irritation
H351 - Suspected of causing cancer
H373 - May cause damage to organs through prolonged or repeated exposure

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals		
STOT RE	Specific target organ toxicity - Repeated exposure		
STOT SE	Specific target organ toxicity - Single exposure		
EWC	European Waste Catalogue		

SAFETY DATA SHEET

EVO-STIK RESIN-W POLYURETHANE WOOD ADHESIVE
Supersedes Date: 16-Nov-2017

Revision date 07-Oct-2019
Revision Number 1.02

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 07-Oct-2019

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet