

Nitromors All Purpose

Paint & Varnish Remover

Date: 19 May 2016

Fact Sheet No.:Version 3

YOUR SMART ADVANTAGES

- Removes most types of decorative paints, gloss, varnish and emulsions
- Non-acid, non-caustic formulation
- Replaces the use of Methylene Chloride based removers

USES

Nitromors All Purpose Paint& Varnish Remover is a thick semi-gel which is suitable for large areas. It is ideal for all woods, furniture and areas such as skirting boards, doors and items with several layers of paint. Additionally it removes paint from metal and cast iron

PRODUCT CHARACTERISTICS

Colour	Off -White
Form	Semi Gel Liquid
Specific Gravity	1.04 approx.
Flammability	-5 degrees centigrade
Product Code	30605651 500ml x12 30605653 1l x6 30605655 4l
Storage/Shelf Life	Store for up to 12 months from date of manufacture in original, unopened packaging under cool, dry, conditions within the temperature range of 5°C to 30°C and out of direct sunlight. Protect from frost.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	5°C to 25°C
Coverage	1 litre covers 2 to 4 square metres dependant on thickness and number of layers of paint
Penetration	Wait at least 30 minutes before checking, but typically up to 2 hours will give good penetration. Do not allow to dry out.
Solvent for Cleaning Up	Water / White Spirit

DIRECTIONS FOR USE

IMPORTANT: Read and follow the Health & Safety instructions as detailed in the separate MSDS document.

PREPARATION

1. Protect Floor Coverings, textiles, plastic, rubber items and any items sensitive to solvents.
2. The product is flammable YOU MUST ensure there are no sources of ignition before using.
3. Agitate container to ensure uniform consistency.

APPLICATION

4. Ideally apply out of direct sunlight.
5. Apply a thick coat by brush. DO NOT BRUSHOUT. The thicker the paint, the more Nitromors you will require. If possible light scoring of the surface will improve penetration.
6. Check a small area with a scraper. If softened, then remove by scraping. A nylon toothbrush can be useful for getting into crevices. Areas of ingrained paint can be rubbed along the grain with steel wool dipped in Nitromors.

7. For multi-layered finishes, further Nitromors can be re-applied without removing the first coat.

CLEANING

8. Wash Down the surface with water and detergent. On fine wooden surfaces however use white spirits to wipe down.

PRECAUTIONS IN USE

For any application not covered please contact Technical Services on +353 1 8624998 or visit www.bostik.ie for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Nitromors Craftsman's, available at www.bostik.ie.



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 01 8624900	Fax: 01 8402186	orders.bostik-irl@bostik.com
Technical Advice	Tel: 01 8624998	Fax: 01 8402186	
Technical Data & COSHH (MSDS) Data Sheets	Tel: 01 8624900	Fax: 01 8402186	



FM 01696
BS EN ISO 9001:2008